



TIPS FOR EPSON CARTRIDGES

HANDY TIPS

1. Only install one cartridge at a time. Close the printer lid so the printer driver can see the new cartridge.
2. Only replace the cartridge the printer is asking for. No need to change all the other tanks.
3. Replace cartridges as soon as they run out of ink. Empty cartridges in the printer can cause blockages.

TAB REMOVAL



It is important to remove the Yellow tab (Air Vent tab) on a cartridge before installation into the printer. Ink can not be drawn into the print head if you fail to peel off the tab. This will cause your print out to be scratchy, have lines through it or appear to be the wrong colour. This information is also clearly marked on the side of every CW inkjet cartridge.



Air vent tab



Air Vent

If a cartridge is accidentally installed without removing the air vent tab, remove the cartridge and pull the tab off. When you do this some ink may be forced from the air vent.



TANK SHAPE

In some cases the cartridge you are removing from your printer and the cartridge you are about to insert may look slightly different, however you will have no difficulty installing the product. Cartridge World cartridges carry the same amount of ink and in some cases more ink than other brands. Fig.3 shows two versions (standard and high yield) of a common OEM tank. You can see they both have a number of empty internal chambers. e.g. not totally filled with ink.



Fig.1



Side view

Fig.2

Top view




Fig.3

Cut away, side view

OEM High Yield

OEM Standard Yield



If you experience printing problems don't remove any cartridges and potentially waste time on an unnecessary trip to the store. Call the store where you purchased the cartridges from.

Remember all Cartridge World cartridges come with a full satisfaction guarantee.